

## Features


- Cuttable every 6 LEDs.
- Bendable with high efficacy LED.
- Long lifespan with great lumen maintenance .
- Input voltage: DC24V.
- Excellent UV resistance.
- Internal constant current for extremely long series connection without light decay.

## Application

- Ideal for Commercial and Residential use in coves, under cabinets, closets, steps, displays, offices etc.

## Installation

- 3M self adhesive tape



## Optical & Electrical Parameters

Model No.	Color Temperature (K)	Beam Angle	CRI/Ra	Luminous Flux (lm/ft)	Efficacy (lm/w)	Max Run	Voltage (DC V)	Power (W/ft)
LR-2835A-120-24	3000	120°	80+ 90+	326	82.5	52' (16m)	24	3
	4000			369	84			
	5000			373	85			
	6500			373	85			
	8000			382	87			

## Other Parameters

Model No.	Quantity(pcs/m)	Standard Series Connection (ft) (Single Feed)	Working Temperature	Storage Temperature
LR-2835A-120-24	120	52	-25~+60°C	-25~+70°C

**NOTE:**

- Above data is typical when testing Type A LED.
- Test environment temperature: 25±2°C
- Actual data of each product may differ from the typical values.
- Data is subject to change without notice.
- Different color temperature will make luminous flux differ.
- Power tolerance within ±10%.

## Profile Drawings

LR-2835A-120-24

Unit:mm

